

Hardwax Oil Extreme is a low-odour product for the oil treatment of wooden floors. It combines all the advantages of oil and wax into a single product, which ensures an extremely robust and resistant surface that is well-protected against spills and stains. Hardwax Oil Extreme emphasises the natural glow of the wood, leaving a comfortable anti-slip surface that is easy to maintain.

- **Good resistance to water, coffee, tea and red wine**
- **Resistant to scratches and marks**
- **Gives the wood a natural appearance and breathable surface**
- **Easy to maintain using associated care products**



Application area

For untreated, new or newly-sanded wooden surfaces, or as a topcoat on top of WOCA Master Colour Oil.

Work description

Preparation	<p>It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time.</p> <p>The floor must be free of dirt, grease, wax and sanding residue. Previously treated floors should be sanded down to bare wood with grain 120-150. Vacuum thoroughly and wipe the floor down afterwards if necessary, using a tightly-wrung water-soaked cloth. Hardwax Oil Extreme is ready for use.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Final sanding	Grit 120-150
Treatment	<p>Hardwax Oil Extreme should be stirred thoroughly before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply a thin and even coat of oil with a short-bristled paint roller (3-4 mm) to a small area of the floor at a time (5-10 m²). Distribute the oil thoroughly. Leave the oil to stand on the surface for 5-10 minutes, while shiny. If the oil soaks quickly into the wood, apply more oil. Please note: After approx. 15 minutes, Hardwax Oil Extreme will begin to seal on the surface. Buff the surface with a white or beige buffer pad until the wood appears saturated. Then buff with a clean lint-free cotton cloths to remove excess oil before proceeding to the next section. The surface should not appear wet and no excess oil should remain on the surface. Leave the floor to dry for 8-10 hours. Repeat the treatment if another layer of oil is required or if you want a higher gloss or tougher surface.</p>
Note	<p>Do not expose the floor to water or clean it for the first 7 days while the oil is hardening. After 7 days, the floor can be cleaned with WOCA Natural Soap or WOCA Oil Refreshing Soap, which gives the surface extra protection.</p>

Drying time

Time before the product takes effect	5-10 minutes. Depending on temperature, humidity and application quantity.
Drying time	8-10 hours. Depending on temperature, humidity and application quantity. Lower temperatures and/or higher humidity can extend drying time.
Fully hard	7 days



Technical data

Binder	Modified vegetable oils and wax
Density	0.9 g/ml
Solid content	Approx. 53%
Shelf life	3 years
Application Temperature	+ 15-30° C
Coverage	Approx. 20 m ² /l, depending on wood type and surface
Colours	Natural and white
Cleaning of tools	WOCA Solvent
Storage	+ 10-25° C. Keep out of reach of children. Must not be exposed to heat [e.g. sunlight]. Store frost-free.
VOC	This product contains a maximum of 515 g VOC/L. The permitted value is 700 g VOC/L [cat. A/f].
Packaging	2.5 L
Migration test of non-desired materials	EN 71-3:2013
Authorisations	Danish Indoor Climate Labelling IBR: TVOC28/A+, AgBB Z-157.10-198

Maintenance and related products

Weekly cleaning	Natural Soap, article no. 511010
Monthly care	Oil Refreshing Soap, article no. 511210
Half yearly care	Oil Care, article no. 528010
Related products	Intensive Wood Cleaner, article no. 551525
Accessories	Paint Roller, 4 mm pile, article no. 88004 Paint roller handle, 25mm, article no. 599650 Telescopic rod, article no. 599651

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.