



Hardwax Oil Swift is a quick drying, low-odour roll-on product for the oil treatment of wooden floors. It is incredibly easy to apply, since it does not need to be rubbed into the wood. Hardwax Oil Swift combines natural oil and wax in a single product, ensuring an extremely robust surface with high resistance to spills and stains. It gives the floor a neutral appearance and a comfortable non-slip surface that is easy to maintain. The product is suitable for base treatment of untreated, new or newly-sanded wooden surfaces, or as a topcoat on top of WOCA Master Colour Oil.

- **Does not need to be rubbed into the wood**
- **Resistant to liquids such as water, coffee, tea and red wine**
- **Resistant to scratches and marks**
- **Gives the wood a natural appearance and breathable surface**
- **Easy to maintain using associated care products**



## Application area

For untreated, or newly-sanded wooden surfaces, or as a topcoat on top of WOCA Master Colour Oil.

## Work description

Preparation	<p>It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. Always remember to test on a less visible spot to check the compatibility of the wood with the oil.</p> <p>The floor must be free of dirt, grease, wax and sanding residue. Previously treated floors should be sanded down to bare wood with grain 120-150. Vacuum thoroughly and wipe the floor down afterwards if necessary, using a tightly-wrung water-soaked cloth.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Final sanding	Grain 120-150
Treatment	<p>Hardwax Oil Swift should be stirred thoroughly before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply a thin layer of oil using a short-bristled paint roller (3-4 mm) or similar, along the grain of the wood. Distribute the oil thoroughly. Leave the floor to dry for 4-5 hours. Repeat the treatment if another coat of oil is required.</p>
Note	<p>Do not expose the floor to water or clean it for the first 7 days while the oil is hardening. After 7 days the floor can be cleaned with WOCA Natural Soap or WOCA Oil Refreshing Soap, which gives the surface extra protection.</p>

## Drying time

Drying time	4-5 hours Depending on temperature, humidity and application quantity.
Fully hard	7 days Depending on temperature, humidity and application quantity. Lower temperatures and/or higher humidity can extend drying time.



## Technical data

Binder	Modified vegetable oils and wax
Density	Approx. 0.9 g/ml
Solid content	43 %
Shelf life	3 years
Application Temperature	15-30° C
Coverage	Approx. 20 m <sup>2</sup> /L, depending on wood type and surface
Colours	Natural and white
Gloss	Matt and Silk-matt
Cleaning of tools	WOCA Solvent
Storage	+ 15-25 °C. Keep out of reach of children. Must not be exposed to heat (e.g. sunlight). Store frost-free.
VOC	This product contains max. 500 g VOC/l. Permitted value is 500 g VOC/l [cat.A/i].

## Maintenance and related products

Weekly cleaning	Natural Soap, article no. 511010
Monthly care	Oil Refreshing Soap, article no. 511210
Half yearly care	Oil Care, article no. 528010
Related products	Intensive Wood Cleaner, article no. 551525
Accessories	Paint Roller, 4 mm luv, article no. 88004 Paint roller handle, 25mm, article no. 599650 Telescopic rod, article no. 599651

## Contact

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*