



Maintenance Gel is for the care and maintenance of oiled indoor wooden surfaces and floors. The oil is quick-drying and leaves an attractive, water and dirt-repellent surface.

Maintenance Gel is suitable for furniture, kitchen work surfaces, floors and other indoor wooden surfaces. It can also be used for improved results on factory-oiled/UV-oiled surfaces.

- **Especially suitable for UV-oiled floors**
- **Excellent results on factory-oiled floors**
- **Makes floors even more durable**
- **Can be applied manually with a polish pad and by machine using a buffer**



## Application area

For care and maintenance of all oiled wood types. Only for indoor use.

## Work description

Preparation	<p>It is important that both wood and oil are at a temperature of at least 15°C, and ideally about 20°C, and that air humidity is approx. 50 %. Make sure that the room is well-ventilated, for optimal evaporation and drying time.</p> <p>Thoroughly clean the surface with Intensive Wood Cleaner, mixed 1 part cleaner to 20 parts water. Then wash with clean water. After cleaning, leave the surface to dry for at least 8 hours, at 20°C. Sand the surface with grain 180 sandpaper. Vacuum clean the surface to remove sanding residue.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Final sanding	Grit 180
Treatment	<p>1. Apply an appropriate amount of gel to a red WOCA Hand Scrubber and distribute over the surface in a thin, even coat. Continue polishing until the wood seems saturated and the surface has a uniform appearance. It is recommended to work on small areas at a time, as the gel dries quickly. For larger areas [floors larger than 10 m<sup>2</sup>] it would be advantageous to use a polishing machine. 2. Immediately wipe down the polished surface with a clean, dry lint-free cotton cloth. When prepping with a machine, the final polishing should be done with a cotton cloth beneath the buffer. The surface should not appear wet and no excess gel should remain on the surface. 3. If the wood does not seem fully saturated after 4-6 hours, it would be advantageous to repolish, with less gel than the first treatment, but following the same procedure. Wait 4-6 hours before using the surface. Avoid getting water or dirt on the wooden surface for the first 2-3 days.</p>
Note	<p>The oiled surface should not be exposed to water for the first 2-3 days, as this can cause stains and discoloration.</p> <p>Wood humidity must not exceed 18%.</p> <p>High temperature and low air humidity will shorten drying times.</p> <p>Low temperature and high air humidity will extend drying times.</p>

## Drying time

Drying time	After cleaning with Intensive Wood Cleaner: 8 hours at 20°C.
Light use	4-6 hours
Fully hard	2 -3 days



## Technical data

Binder	Vegetable oil components, isoparaffin, cobalt-free drying agent.
Density	0.9-1.0 g/ml
Shelf life	3 years
Application Temperature	+ 15-30°C
Viscosity	Approx. 20 sec.
Coverage	20-30 m <sup>2</sup> /L
Colours	Natural and white
Cleaning of tools	Clean in turpentine
Storage	+ 10-25°C. Keep out of reach of children. Must not be exposed to heat (e.g. sunlight). Store frost-free.
VOC	This product contains max. 135 g VOC/L. Permitted value is 500 g VOC/L (cat.A/i).
Packaging	200 ml.
Authorisations	Foodstuffs approved Indoor climate certification

## Maintenance and related products

Weekly cleaning	Natural soap, item no. 511025 Natural soap Spray, item no. 510900
Monthly care	Oil soap, item no. 511225
Related products	Intensive Wood Cleaner, item no. 551525
Accessories	Red hand scrubber, item no. 599755 Polishing cloth, grey, item no. 596057

## Contact

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*