## **Product specification sheet**




- Profile type:

**578** 







Product group: Design-Clip® (Trademark of Küberit)

- **Description:** connecting profile, a patented two part clip system for

floating installation of floorings

- **Application:** transition or connections of floorings, especially for click

LVT and carpets

- **Length:** 3.0 m / 2.7 m / 1.0 m / 0.9 m

- **Width:** 24 mm

- **Expansion:** 2 x 6 mm

- For floor thickness: LVT 4 to 7.5 mm with a 2 mm underlay

Carpets 5 to 12 mm

- Material: aluminium

Alloy of the profile: AlMgSi0,5F22

- Aluminium colors: anodized in F4 silver, F5 gold, F6 bronze,

F2G stainless steel optic mat brushed, F9 sand

as well as F3 polished

Wood decors: 5 wood decors are available, see brochure or website for

more information

- Digital printed decors: colour matching decors with digital printed technology

possible with abrasion surface of AC3 to AC5

Datum/date: 18.05.2017



Küberit Profile Systems GmbH & Co. KG

Römerweg 9

58513 Lüdenscheid, Germany Tel.: +49 23 51 / 95 07 - 0

Fax: +49 23 51 / 95 07 – 200

Seite/page 1 von/of 2 © Küberit 2017

www.kueberit.com

## **Product specification sheet**



The indicated data are typical or average values, but are not assured attributes.

This product is not subject to the Construction Products Regulation.

## Installation

- 1. Screw or dowel the base profile (=plug mounting). In case of floor heating, fix the profile by using a 2-components glue.
- 2. Adapt the hard floor covering and pay attention to the expansion joint.
- 3. Put the top profile carefully on the base profile, bring it first into the right position, then clip-in the top profile by well controlled hammer blows.

  Attention: Never use the hammer directly but use a hardwood with felt.
- 4. Finished!

For further information of the installation use the brochure Design-Clip® from our website or additional installation information as well as our installation video.

Datum/date: 18.05.2017