
Product specification sheet



Profile type:

588





- **Product group:** Euro-Clip® (Trademark of Küberit)

- **Description:** connecting profile (T-profile), a patented two part clip

system for floating installation of floorings

- **Application:** for all hard floor coverings connecting two floating floors or

a floating floor to a glued floor as f.e. ceramic tiles

- **Length:** 3.0 m / 2.7 m / 1.0 m / 0.9 m

- **Width:** 44 mm

- **Expansion**: 2 x 10 mm

For flooring heights: 10 to 16 mm with a 2 mm underlay

- **Material:** aluminium

- Alloy of the profile: AlMgSi0,5F22

- Aluminium colors: anodized in F4 silver, F5 gold, F6 bronze,

F2 stainless steel optic, F9 sand

as well as F3 polished

Wood decors:
 15 wood decors are available, see brochure or

website for more information

- Digital printed decors: colour matching decors with digital printed technology

possible with abrasion surface of AC3 to AC5

DIGITAL PRINT

Decor coating by Küberit

Küberit Profile Systems GmbH & Co. KG Römerweg 9

Komerweg 9

58513 Lüdenscheid, Germany Tel.: +49 23 51 / 95 07 - 0 Fax: +49 23 51 / 95 07 - 200 Seite/page 1 von/of 2

© Küberit 2018

Datum/date: 22.03.2018 www.kueberit.com

Product specification sheet



The indicated data are typical or average values, but are not assured attributes.

This product is not subject to the Construction Product Regulation.

Installation

- 1. Screw or dowel the base profile (=plug mounting). In case of floor heating, fix the profile by using a 2-components glue.
- 2. Adapt the hard floor covering and pay attention to the expansion joint.
- 3. Put the top profile carefully on the base profile, bring it first into the right position, then clip-in the top profile by well controlled hammer blows.

 Attention: Never use the hammer directly but use a hardwood with felt.
- 4. Finished!

For further information of the installation use the brochure Euro-Clip[®] from our website or additional installation information as well as our installation video.

Tel.: +49 (0) 23 51 / 95 07 - 0 Fax: +49 (0) 23 51 / 95 07 - 49

Datum/date: 22.03.2018